



Standard 52.5 Minimum Efficiency Reporting Value	Dust Spot Efficiency	Arrestance	Typical Controlled Contaminant	Typical Applications and Limitations	Typical Air Filter/Cleaner Type
20	n/a	n/a	< 0.30 pm particle size	Clean rooms	>99.999% eff. On 10-.20 pm - Particles
19	n/a	n/a	Virus (unattached)	Radioactive Materials	? 99.999% off. On .30 pm Particles
10	n/a	n/a	Carbon Dust :	Pharmaceutical Man.	>99.99% eff. On .30 pm Particulates
17	n/a	n/a	All Combustion smoke	Carcinogenetic Materials	>99.97% elf. On .30 pm Particles
16	n/a	n/a	.30-1.0 pm Particle Size	General Surgery	<b>Bag Filter-</b> Nonsupported
15	>95%	n/a	All Bacteria	Hospital Inpatient Care	micro fine fiberglass or synthetic media, 12- 36 in.
14	90-95%	>98%	Most Tobacco Smoke	Smoking Lunges	deep, 6-12 pockets <b>Box Filter-</b> Rigid Style
13	89-90%	>93%	Proplet Nuclei (Sneeze)	Superior Commercial Buildings	Cartridge Filters 6 to 12' deep may use lofted or paper media.
12	70-75%	>95%	1.0-3.0 pm Particle Size • Legionella	Superior Residential	<b>Bag Filter-</b> Nonsupported micro fine fiberglass-or synthetic media, 12- 36 in.
11	60-65%	>95%	Humidifier Dust Lead Dust	Better Commercial Buildings	deep, 6-12 pockets <b>Box Filter-</b> Rigid Style
10	50-55%	>95%	Milled Flour Auto Emissions	Hospital Laboratories	Cartridge Fitters 6 to 12" deep may use lofted or paper media.
9	40.%	>90%	Welding Fumes		
8	30-35%	>90%	3.0-10.0 pm Particular Size	Commercial Buildings	<b>Pleated Filters-</b> Disposable, extended surface area, thick with cotton-polyester blend media, cardboard cardboard frame
7	25-30%	>90%	Mold Spores Hair Spray	Better Residential	<b>Cartridge Filters-</b> Graded density viscous coated cube or pocket filters, synthetic media
6	<20%	85-90%	Fabric Protector. Dusting Aids	Industrial Workplace	<b>Throwaway-</b> Disposable synthetic panel filter.
5	<20%	80-85%	Cement Dust Pudding Mix	Paint Booth Inlet	
4	<20%	75-80%	>10.0 pm Particle Size	Minimal Filtration	<b>Throwaway-</b> Disposable fiberglass or synthetic panel filter.
3	<20%	70-75%	Pollen Dust Mites	Residential	<b>Washable-</b> Aluminum Mesh
2	<20%	65-70%	Sanding Dust Spray Paint Dust		
1	<20%	<65%	Textile Fibers Carpel Fibers	Window NC Units	<b>Electrostatic-</b> Self charging woven panel filter.